

Colour code DIN (IEC 60304)


Fibres												Tubes		
1	2	3	4	5	6	7	8	9	10	11	12	1	2	...
RD	GN	BU	YE	WH	GY	BN	VT	TQ	BK	OG	PK	RD	GN	WH
13	14	15	16	17	18	19	20	21	22	23	24			
RD	GN	BU	YE	WH	GY	BN	VT	TQ	TP	OG	PK			

Fibres 13-24 are ring marked (black).

Art. No.	Description	Connector type	Connector colour	Boot colour	Zero-fibre colour	IL mean [dB]	IL max. [dB]	RL mean [dB]	RL min. [dB]
49561800ZY	FO trunk cable, 12x LCD/APC, G.652.D, A to B, Dca	LCD/APC	Green	Green	Yellow	0.12	0.25	70	65
49561900ZY	FO trunk cable, 12x LCD/PC, G.652.D, A to B, Dca	LCD/PC	Blue	Blue	Yellow	0.12	0.25	55	50
49562000ZY	FO trunk cable, 12x LCD/PC, OM3, A to B, Dca		Beige	Beige	Turquoise	0.15	0.25	35	30
49562100ZY	FO trunk cable, 12x LCD/PC, OM4, A to B, Dca				Heather violet				

Note: This list may not show all existing articles.

Art. No.	Cable description	CPR class	Sheath colour	Sheath Ø [mm]
18735400DZ	FO Universal-Z 1x24 E9 G.652.D GN / U-DQ(ZN)BH	Dca-s2,d1,a1	Green	8.2
19175500DZ	FO Universal-Z 1x24 G50 OM3 GN / U-DQ(ZN)BH			
19271300DZ	FO Universal-Z 1x24 G50 OM4 GN / U-DQ(ZN)BH			

<div> DATWYLER</div> <div>Dätwyler IT Infra, itinfra.datwyler.com</div>	Description FO trunk cable, 12x LCD, G.652.D, OM3, OM4, A to B, Dca						
Drawn	Philipp Bless	11.04.2025	Drawing name		DRW_FO_TC_12LCD_A-B_D		
Checked	André Jaun	15.04.2025	Size	Scale	Article number	Document number	Revision
Approved	Kai Wirkus	17.04.2025	A3	-	According to table	-	00
						00	1 of 1