

KS-TS 1/8 tool-less slimline Cat.6/E

RJ45 module, shielded, Category 6/E





KS-TS 1/8 tool-less slimline Cat.6/EA RJ45 module





Description

For the transmission of digital and analogue voice-, video- and data signals.

The KS-TS RJ45 module is designed to shorten the termination and installation times.

It exceeds the IEC 60603-7-5 standard's requirements for Cat. 6 connecting hardware up to 250 MHz. It also fulfils all Class EA Channel requirements up to 500 MHz when combined with Cat. 7 or Cat. 7A data cables. Therefore it is applicable for 10-gigabit Ethernet transmissions in accordance with IEEE 802.3.

Useable for Power over Ethenet Plus (PoE+) corresponding to IEEE 802.3at. Solid zinc die casting housing with mounting clip for installation in Keystone panels and outlets.

Compact construction for high packing density in faceplantes/outlets (up to 3 modules).

Contact spring with phosphor bronze alloy, plated with gold.

For connecting the wires a wire manager is used in combination with two integrated moveable housing wings for tool-less IDC connections.

Only for cutting the wires a plane wire cutter is necessary.

Strain relief via cable tie. The module is re-usable.

| General properties | |
|---------------------------|-----------------|
| Installation temperature | -10 °C - +60 °C |
| Storage temperature | -40 °C - +70 °C |
| Operating temperature | -20 °C - +60 °C |

| Electrical properties | |
|-----------------------|-----------------|
| GBit/s | Up to 10 Gbit/s |
| Shielding | shielded |

| Mechanical properties | | | | |
|------------------------------|---|--|--|--|
| Connection type | IDC insulation displacement connectors | | | |
| Solid copper wire | 0.50 (AWG 24) - 0.65 (AWG 22) | | | |
| Stranded copper wire | AWG26/7 | | | |
| Diameter over Insulation | 0.70 mm - 1.40 mm | | | |
| Re-connection | for AWG 22, AWG 23 and AWG 24 when using the same or bigger wire diameter | | | |
| Re-usable | once | | | |



| Standards | |
|---------------------|--|
| Cat./Class | Cat.6 / Class E _A |
| PoE | IEEE 802.3bt Type 4 (100W) |
| Connector standards | IEC 60603-7-5, IEC 60512-99-001 |
| Cabling standards | ISO/IEC 11801, EN 50173-1, TIA/EIA 568-x |

| Versions | | | | | | | | |
|-----------------|---|--------|-------------|--------------|----------------|--|--|--|
| Material number | Product | Colour | Weight [kg] | Packing unit | GTIN / EAN | | | |
| 41805400ZF | RJ45 module KS-TS 1/8 tool-less slimline Cat.6/E _A shielded | silver | 0.03 kg | 12 pcs. | 40393910087963 | | | |
| 418054 | RJ45 module KS-TS 1/8 tool-less slimline Cat.6/E _A shielded | silver | 0.03 kg | 10 pcs. | 40393910165142 | | | |

Subject to technical modification As of 2023-09-14 08:02:51