

Defined Disconnect CP-Link

Cable adaptador IP20



Imagen similar

Description

Releases the connection of patch cable and socket above a certain tensile force and thus protects circuit boards and sockets from damage. Particularly compact adapter cable.

Meets the Channel performance requirements of ISO 11801 and EN 50173 Class EA despite its extremely small dimensions.

Impresión de aplicaciones

Sorry, this product is not available in your country. In medical technology, sound studio technology and measuring technology as well as in the connection of computer systems.

Reliably separates any connection above a defined tensile force to protect the equipment.

The restraining force is set in such a way that unintentional triggering is prevented.

Pull out force 20 N +15/-10 N.

Propiedades generales

Construcción del cable	4x2
Manguito anti-torceduras	Moulded-on
Tipo de cable	S/FTP
Tipo de conector, conexión 1	RJ45 8(8)
Tipo de conector, conexión 2	RJ45 8(8)

Propiedades eléctricas

Asignación de pin	1:1
Categoría	6A (IEC)
EMC	blindado

Estándares

Cat 6A	IEC 61935-3
Clase EA	EN 50173-1, ISO/IEC 11801
Cero halógeno gases no corrosivos	EN 60754-1/-2, IEC 60754-1/-2, VDE 0482-754-1/-2
Estándares de cableado	EN 50173-1, ISO/IEC 11801

Versions

Número de material	Producto	Connector type side A	Connector type side B	Libre de halógenos	Peso [kg]
418089	Defined Disconnect CP-Link	RJ45 F	RJ45 M	Yes	0,04 kg