

Defined Disconnect CP-Link

Cavo adattatore IP20



Description

Releases the connection of patch cable and socket above a certain tensile force and thus protects circuit boards and sockets from damage. Particularly compact adapter cable.

Meets the Channel performance requirements of ISO 11801 and EN 50173 Class EA despite its extremely small dimensions.

Applicazione

In medical technology, sound studio technology and measuring technology as well as in the connection of computer systems.

Reliably separates any connection above a defined tensile force to protect the equipment.

The restraining force is set in such a way that unintentional triggering is prevented.

Pull out force 20 N +15/-10 N.

Proprietà generali

Anti-kink sleeve	Moulded-on
Cable type	S/FTP
Costruzione di cavi	4x2
Type of connector connection 1	RJ45 8(8)
Type of connector connection 2	RJ45 8(8)

Proprietà elettriche

Category	6A (IEC)
EMC	shielded
Gbit/s	Up to 10 Gbit/s
Pin assignment	1:1

Standards

Cat 6A	IEC 61935-3
Class EA	ISO/IEC 11801, EN 50173-1
Zero halogen no corrosive gases	IEC 60754-1/-2, EN 60754-1/-2, VDE 0482-754-1/-2
Cabling standards	ISO/IEC 11801, EN 50173-1

Versions

Numero Materiale	Product	Raccordo tipo laterale A	Raccordo tipo laterale B	Halogen free	Peso [kg]
418089	Defined Disconnect CP-Link	RJ45 F	RJ45 M	Yes	0,04 kg