

Defined Disconnect CP-Link

Adapter cable, IP20



Gelijkaardig beeld

Beschrijving

Releases the connection of patch cable and socket above a certain tensile force and thus protects circuit boards and sockets from damage. Particularly compact adapter cable.

Meets the Channel performance requirements of ISO 11801 and EN 50173 Class EA despite its extremely small dimensions.

Toepassing

In medical technology, sound studio technology and measuring technology as well as in the connection of computer systems.

Reliably separates any connection above a defined tensile force to protect the equipment.

The restraining force is set in such a way that unintentional triggering is prevented.

Pull out force 20 N +15/-10 N.

Algemene eigenschappen

Anti-knik mouw	Moulded-on
Kabel constructie	4x2
Kabeltype	S/FTP
Type aansluiting, aansluiting 1	RJ45 8(8)
Type connector, aansluiting 2	RJ45 8(8)

Elektrische eigenschappen

Categorie	6A (IEC)
EMC	geschermt
Pin toewijzing	1:1

Normen / Standaards

Cat 6A	IEC 61935-3
Klasse EA	EN 50173-1, ISO/IEC 11801
Nulhaloogen geen corrosieve gassen	EN 60754-1/-2, IEC 60754-1/-2, VDE 0482-754-1/-2
Bekabeling standaard	EN 50173-1, ISO/IEC 11801

Versions

Materiaal nummer	Artikel	Stekker type kant A	Stekker type kant B	Halogeenvrij	Gewicht [kg]
418089	Defined Disconnect CP-Link	RJ45 F	RJ45 M	Yes	0,04 kg