

FO-DCS 3U/7HP BO plug-in-modules, 6x LCD/APC

for FO-DCS modular subracks / panels, OS2, APC Version



High-Performance FO-DCS BO plug-in modules LCD, 3U/7HP

Description

Open polycarbonate housing (PC) and front panel 3U / 7HP in polycarbonate (black).
 The radius limiter on the rear side and the integrated clips ensure a simple and safe handling of the pre-assembled legs.
 The front panel is fitted with 6 LCD adapters and provides two integrated labelling strips on both sides of the LCD ports for customer-specific printing.
 Fixation with two knurled screws (captive).

Application

FO-DCS breakout plug-in modules LCD (12F 3U/7HP) are suitable for all high-performance applications with duplex signals, particularly in the data centre environment.
 They find modular application in FO-DCS modular panels (19"/1U) or in FO-DCS subracks (19"/3U, 19"/4U).
 They are used to accept pre-assembled LC/LCD trunk cables.
 Packing densities of up to 144 fibres on 3U are achieved with these plug-in modules.

General Properties

Acceptance capacity	6 duplex ports (12 fibres)
Fully equipped	Yes

Optical Properties

Adapter, front side	6 x LCD/APC, green (Dust plug)
Adapter colour, front side	green
Adapter material, front side	Polymeric
Adapter type, front side	LCD/APC
Fibre type	OS2
Number of adapters, front side	6
Sleeve material, front side	Zirconia (ZrO ₂)

Mechanical properties

Dust protection, frontside	Yes
Dust/Laser protection, frontside	Dust plug
Laser protection, frontside	No

Scope of delivery

Housing with front panel, equipped with 6 LC duplex adapters (ceramic sleeves).
All ports are fitted with two transparent dust protection plugs (front/rear).
Rear side with integrated radius limiter and clips for the pre-assembled legs.
Optional LCD laser protection clips (metal) can be obtained and retrofitted.

Note

As a high-performance patch cable we recommend the FO-DCS LCD Uniboot patch cables.

Versions

Material number	Product	Outer dimensions	Colour	Material	Weight [kg]	Packing unit
571579	FO-DCS 80 plug-in-module LCD 3U/7HP, 6x LCD/APC, green	3 U, 129 mm x 35 mm x 182 mm	black	Polycarbonate (PC)	0.15 kg	1 pc.

Subject to technical modification

As of 2021-07-01 11:14:09