

ODF subracks, Easy Access

1U, 2U, 3U, 48-144 fibres



High-density subrack for Datwyler ODF

Description

The Datwyler ODF subracks are particularly suitable for high-density applications in telco/carrier networks. They provide advanced splice and patch systems and cable management. Smooth and convenient telescopic sliding system. Cable glands to secure the incoming fibres. Strain relief for all cables. Bend radius control for fibres.

Application

Backbone and distribution networks, particularly for PoPs in the carrier section. Also suitable for data centres and LAN projects (19).

Propriétés générales

Capacité	24 ports per tray - 1U up to 48, 2U up to 96, 3U up to 144 fibres (72 duplex adapters)
Colour	Light grey, RAL 7035 (powder-coated)

Versions

Numéro de matériau	Produit	Nombre d'adaptateurs	Adaptateurs	Nombre de fibres	Dimensions extérieures	Poids [kg]
19694600ZY	ODF subrack, Easy Access	24	LCD/APC	48	1 U	6,65 kg
19694500ZY	ODF subrack, Easy Access	48	LCD/APC	96	2 U	6,4 kg
19694400ZY	ODF subrack, Easy Access	72	LCD/APC	144	3 U	6,1 kg

Sous réserve de modifications techniques

A partir de 2021-01-27 11:41:56