

DCS patch cable MTP, 12 fibres OM4

High-performance



DCS patch cable (FR/LSZH), 12 fibres OM4

Description

Thin, very flexible fibre-optic patch cable (round cable, Ø 2.0 mm) with 12 fibres. Each patch cable is equipped with push-pull tabs.

Low fire load due to its halogen-free flame-retardant LS0H sheath.

Available with up to 5 m standard lengths (other lengths on request).

Sticker labelling at both cable ends.

Standard polarisation modes can be type A, B or type C.

Application

MTP-on-MTP patch cables are suitable for all high-performance applications with parallel optic signals in a data centre environment. The round patch cables are pre-assembled with high-performance MTP connectors (female) at both ends. They are assembled to a very high quality and guarantee optimum values for optical performance (IL/RL).

Construction				
Cable	round			
Outer sheath colour	heather violet			
Outer sheath material	FR/LSZH			

Optical Properties	
Connector type side A	MTP ₁₂ female
Connector type side B	MTP ₁₂ female
Ferrule polishing connector A	Elite PC 0°
Ferrule polishing connector B	Elite PC 0°
Fibre type	G50/125 OM4
IL maximal, connector A	0.25 dB
IL maximal, connector B	0.25 dB
IL typical, connector A	0.15 dB
IL typical, connector B	0.15 dB
RL minimal, connector A	35 dB
RL minimal, connector B	35 dB
RL typical, connector A	45 dB
RL typical, connector B	45 dB
Standard connector A	IEC 61754-7, IEC 61755-3-31, IEC 611755-3-32
Standard connector B	IEC 61754-7, IEC 61755-3-31, IEC 611755-3-32



Mechanical properties	
Housing colour connector A	magenta
Housing colour connector B	magenta

Scope of delivery

DCS patch cable (FR/LS0H) with 12 fibres OM4 High-performance connector assembly with MTP Elite. All connectors incl. push-pull tabs. Sticker labelling at both cable ends.

Standards				
Zero halogen no corrosive gases	IEC 60754-1/-2			
Flame Propagation	IEC 60332-1-2			
Flame Spread	IEC 60332-3-22 Cat. A			
Smoke Density	IEC 61034-1/-2			

Versions								
Material number	Product	Length (m)	Polarity	Weight [kg]	Packing unit			
473200	DCS patch cable MTP - MTP	1	A	0.01 kg	1 pc.			
473201	DCS patch cable MTP - MTP	2	A	0.02 kg	1 pc.			
473202	DCS patch cable MTP - MTP	3	A	0.02 kg	1 pc.			
473203	DCS patch cable MTP - MTP	4	A	0.03 kg	1 pc.			
473204	DCS patch cable MTP - MTP	5	A	0.03 kg	1 pc.			
473210	DCS patch cable MTP - MTP	1	В	0.01 kg	1 pc.			
473211	DCS patch cable MTP - MTP	2	В	0.02 kg	1 pc.			
473212	DCS patch cable MTP - MTP	3	В	0.02 kg	1 pc.			
473213	DCS patch cable MTP - MTP	4	В	0.03 kg	1 pc.			
473214	DCS patch cable MTP - MTP	5	В	0.03 kg	1 pc.			
473220	DCS patch cable MTP - MTP	1	С	0.01 kg	1 pc.			
473221	DCS patch cable MTP - MTP	2	С	0.02 kg	1 pc.			
473222	DCS patch cable MTP - MTP	3	С	0.02 kg	1 pc.			
473223	DCS patch cable MTP - MTP	4	С	0.03 kg	1 pc.			
473224	DCS patch cable MTP - MTP	5	С	0.03 kg	1 pc.			

MTP* and MTP Elite* are registered trademarks of US Conec Ltd.

Subject to technical modification As of 2021-10-01 07:08:51