

Phone panels CU 25/4

unshielded, loaded with 25 RJ45 jacks, Category 3



Phone panel CU 25/4

Descrizione

Unshielded 19"/1U phone panels for the transmission of digital (ISDN) and analogue voice signals.

Especially suitable for all Class C applications in accordance with EN 50173-1 and ISO/IEC 11801.

The patch panels support cables up to 50 pairs (telephone cables).

A maximum of four wires may be connected to one RJ45 socket. A termination aid is available as an optional accessory. This consists of two angular sheets that can easily be fixed to the frame or cabinet and make the cable termination more comfortable. For more accessories see below.

Proprietà generali				
Caricato / Scaricato	Loaded - RJ45 Cat.3			
Design	dritto			
Numerous di monto	25			

Proprietà elettriche	
Category	3
EMC	unshielded

Proprietà meccaniche				
Connection type	LSA			
Mounting method	482.6 mm (19 inch) mounting			
Screened	No			
Type of connector	RJ45 8(8)			

Standards Cat./Class better than Cat.3

Versioni							
Codice art.	Prodotto	Dimensioni esterne	Colore	Peso [kg]	Packing unit		
418000	Phone panel CU 25/4 with 25x RJ45 jacks, Cat.3	1 U, 44 mm x 482 mm x 129 mm	grigio chiaro	1,3 kg	1 pc.		
418002	Phone panel CU 25/4 with 25x RJ45 jacks, Cat.3	1 U, 44 mm x 482 mm x 129 mm	nera	1,35 kg	1 pc.		

Con riserva di modifiche tecniche A partire da 2021-09-17 11:22:38