

Splice box OV-E

19"/1 U, E9/125 G.652.D BLO OS2, LCD/PC

with adapters and pigtails





Description

For the termination of fibre optic cables - maximum of 48 fibres.

Loaded with FO adapters, ready for splicing, with prepared pigtails (per 2 m, colour code: Swisscom).

Telescopic, folding drawer with stop.

Shelf for excess tube lengths below the drawer.

Cable mounting plate at the rear.

Splice cassettes are hinged, can be easily folded up.

General properties				
Outer dimensions (HxWxD)	1 U, 42 mm x 482 mm x 250 mm			
Housing	Aluminium, black, extractable drawer with locking mechanism, box allows for depth-adjust able mounting (5 steps, maximum 50 mm)			
Front plate	Aluminium, white			
Imprint	numbers (silk screen printing) on front plate			
Cable entry	rear left and right pre-stamped cable entries and an enclosed breakout cable entry			
Strain relief	by screwed cable gland			
Capacity	up to 48 fibres			
Labelling strip included	yes			
Mounting set included	yes			
Splice protectors included	yes			
Extractable drawer	yes			
Fold-down drawer	yes			



Singlemode			
E9/125 G.652.D BLO			
OS2			
Swisscom			
LCD/PC			
blue			
Zirconia			
0.25 dB			
0.12 dB			
50 dB			
55 dB			

Scope of delivery

Splice box with

- one straight cable entrie (2 x M15 + 1 x M20)
- one breakout cable entry
- coloured pigtails with measurement report
- FO adapters, fastened by screws
- complete splicing set with crimp splice protection
- labelling strip, 410 mm
- M6 mounting set

Versions										
Material number	Product	Colour (Frontplate)	Number of adapters	Adapter orientation	Pigtails	Weight [kg]	Packing unit	GTIN / EAN		
41516002ZY	Splice box OV-E 6xLCD/PC	silver	6	offset horizontal	12 x LC	2.5 kg	1 pc.	40393910013658		
41516402ZY	Splice box OV-E 12xLCD/PC	silver	12	offset horizontal	24 x LC	3.49 kg	1 pc.	40393910013573		
41516802ZY	Splice box OV-E 24xLCD/PC	silver	24	offset horizontal	48 x LC	3.49 kg	1 pc.	40393910013498		

Variants on request.









Subject to technical modification As of 2023-02-15 09:29:01